

P305

PRODUCT DESCRIPTION

This product is a temporary protective mask designed for use on smooth and semi-smooth surfaces. It is excellent for #3 semi-polished and #4 brushed/satin stainless steel, painted aluminium, and similar surfaces. P305 is available in clear and blue LDPE film with an acrylic adhesive system that allows for clean removal with minimal adhesion buildup. The film contains a 60-day UVI additive that provides clean removal of the tape after prolonged exposure to sunlight.

SPECIFICATIONS

Colours:	Blue, Clear, White
Nominal Thickness:	3 mil
Adhesion	5 oz/in
Tensile Strength	11 lbs/sq in
Elongation	325%

PERFORMANCE FEATURES

P305 is available in clear and blue LDPE film with an acrylic adhesive system that allows for clean removal with minimal adhesion buildup. The film contains a 60-day UVI additive that provides clean removal of the tape after prolonged exposure to sunlight

RECOMMENDED END APPLICATIONS

This product is a temporary protective mask designed for use on smooth and semi-smooth surfaces. It is excellent for #3 semi-polished and #4 brushed/satin stainless steel, painted aluminium, and similar surfaces.

DISCLAIMER

The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their intended use. Protective Packaging assumes no liability for claims beyond the replacement value of our product proved to be defective.