




BERING CONSTRUCTION	STAINLESS STEEL WET	QUARRY TILE DRY	QUARRY TILE WET	QUARRY TILE OIL & WET	Test done by Satra on <b>March 14, 2023</b> Test method for slip resistance: <b>EN ISO 13287: 2019 (Standard 0.30)</b>
	<b>0.62</b> <b>0.61</b>	<b>0.75</b> <b>0.74</b>	<b>0.43</b> <b>0.35</b>	<b>0.27</b> <b>0.26</b>	

## GOLDEN S41540-11, 17

Size: 3-16\*

Colour: Black (11), Orange (17)

\*New sizes: 3, 15 & 16

Height: 15"/38 cm

Width: M

Weight: 3.20 LB



HANGING RING FOR  
BOOT DRYING



S41540-11

S41540-17

- Lightweighted and waterproof PU boot, blended for a greater abrasion, tear, oil and acid resistance.
- Rigid internal METATECH System Plus metguard protection, protects the top as well as the sides of the foot.
- Composite toe protector and puncture-resistant insole.
- Antitortion polypropylene insole integrated into puncture-resistant insole.
- Antimicrobial treated lining.
- Removable insole made of PU foam for a long-lasting comfort.
- 90° heel angle.
- Slip resisting and stable PU outsole blended for a greater abrasion and tear resistance.
- Inner eyelet for hanging; eases the drying process.
- Breathable neoprene insulated Neo sox included.



**METATECH**  
SYSTEM PLUS

